

The JFOPT SFP BIDI 155M 1310/1550nm 2/15/40/80km LC/SC Transceiver series is a compact, small form-factor pluggable module designed for single-fiber bi-directional communication.

The OPT155-3120xxCR series is the high-performance and cost-effective single-mode 1×9 optical transceiver for serial optical communication applications. They are suitable for 100Base-LX Fast ...

The SFP-BIDI transceivers are high-performance, cost-effective modules supporting a dual data rate of 155Mbps and a 20km transmission distance with SMF. The transceivers are compatible with SFP ...

Measured with a PRBS 223-1 test pattern @155Mbps, BER $\leq 1 \times 10^{-10}$. Internally AC-coupled. The transceivers provide serial ID memory contents and diagnostic information about the present ...

155M SFP BiDi 20km Tx1310/Rx1550 o Supports data rates of 155Mb/s o Hot-pluggable o Built-in digital diagnostic functions

The PHILISUN SFP BIDI 155M 1310/1550nm 2/15/40/80km LC/SC Transceiver series is a compact, small form-factor pluggable module designed for single-fiber bi-directional communication.

They are suitable for 100BASE-EX Fast Ethernet, SDH STM-1, SONET OC-3, and ATM (Asynchronous Transfer Mode) designs at the 155Mb/s rate. This series 1×9 industrial transceiver module provides a ...

OptixCom's SFP transceivers are compliant with SFP Multi-Source Agreement (MSA). The BIDI transceivers utilize advanced filter optics to separate the two wavelength with more than 40 dB of ...

Supporting 2km transmission over multimode fiber at 1310nm wavelength, this dual-rate 100/155M SFP module provides 14 dB link budget with speeds from 100-155Mbps. IEEE 802.3u compliant with ...

The JFOPT SFP 155M 1310nm LC DX MM Transceiver series is a compact, small form-factor pluggable module designed for duplex optical data communication, supporting applications such as Fast ...

Web: <https://cgaroofing.co.za>